

FROST

Fighters

ICE



Portable Vented Heaters

- Construction
- Industry
- Mining
- Aviation
- Agriculture
- Military



Clean, Safe, Reliable Portable Heat – wherever you need it – indoors or out!

FROST

Fighters

**Clean, Safe,
Economical,
High Capacity**

- Clean burning flame retention burner.
- Vented burning for safe use in confined areas.
- Independent fan and combustion air feeds ensure quick winter starts. No heated air led off for combustion or lost up the flue.
- Service is a breeze.
- Fast parts supply.

Unlike a direct-fired heater, the Frost Fighter provides clean air, free from moisture and contaminated fumes. Quick connect ducts attach to the front cap outlets and enable the user to disburse the heated air over a large area, with an optional remote thermostat control for maintaining desired temperature levels.

The Frost Fighter is portable and simple to operate – all parts have easy access for quick service and routine maintenance.

With over 25 years of proven reliability and rugged durability even in extreme climates, the Frost Fighter continues to be a leader for temporary heating needs.

Meets OSHA Standards

Specifications

Model	OHV 350-11 OIL	OHV 500 OIL	OHV 350 LP/NG	OHV 500 LP/NG
Code Number	47003	47004	47005	47006
Capacity	320,000 BTU's	420,000 BTU's	350,000 BTU's	450,000 BTU's
Heated Air (w/out duct)	2,000 CFM	2,800 CFM	2,500 CFM	2,800 CFM
Discharge Temp.	200° F with duct creating 0.4" static pressure	180° F with duct creating 0.5" static pressure	220° F with duct creating 0.4" static pressure	235° F with duct creating 0.5" static pressure
Fuel	Fuel Oil*	Fuel Oil*	Propane/ Natural Gas	Propane/ Natural Gas
Tank Capacity	35 Imperial – 42 U.S. gallons (18 Hours)	35 Imperial – 42 U.S. gallons (14 Hours)	Not Applicable (Storage Box)	Not Applicable (Storage Box)
Nozzle Size/ Pressure	2.0 U.S. GPH @ 125 psi	2.5 U.S. GPH @ 145 psi	L/P - 2.5"w.c. N/G - 1.85"w.c.	L/P - 3.2"w.c. N/G - 2.85"w.c.
Burner Motor (115V, 60 cycle)	1/4 HP, 3450 RPM	1/4 HP, 3450 RPM	1/4 HP, 3450 RPM	1/4 HP, 3450 RPM
Fan Motor (115V, 60 cycle)	1/2 HP, 1800 RPM	1 HP, 3450 RPM	1/2 HP, 1800 RPM	1 HP, 1800 RPM
Net Weight (approx)	400 lbs	400 lbs	400 lbs	400 lbs
Shipping Weight (approx)	460 lbs	460 lbs	460 lbs	460 lbs
Finish	Powder Coat	Powder Coat	Powder Coat	Powder Coat
Assembly Material	Color Bond/ Satin Coat	Color Bond/ Satin Coat	Color Bond/ Satin Coat	Color Bond/ Satin Coat
Flue Size	6" diameter	6" diameter	6" diameter	6" diameter
Heavy Duty Tires	12" diameter	12" diameter	12" diameter	12" diameter
Air Outlets - Optional	Standard - Two 12" diameter One 16" diameter	Standard - Two 12" diameter	Standard - Two 12" diameter	Standard - Two 12" diameter
Dimensions crated (LxWxH)	70" x 35" x 50"	70" x 35" x 50"	70" x 35" x 52"	70" x 35" x 52"
Approval	CSA	CSA	ETL	ETL

*No. 1 fuel oil or kerosene is recommended when the ambient temperature is less than 8°F (-10°C) Discharge temperature (@50°F ambient). Specifications are subject to change without prior notice.

Optional Equipment:

Canvas Duct LP/NG Hose	Damper Fan Inlet Ring	Lifting Harness Tool Kit	Remote Thermostat 3' Stack w/Chiria Cap
---------------------------	--------------------------	-----------------------------	--

Your dealer/distributor is:

ECOS
Environmental Containment Systems, Inc.
148 Millrock Road - Old Saybrook, CT 06476

SALES • SERVICE • RENTAL
Supplier of Abrasive Blasting Equipment

1-800-414-0672

www.ecsdustcollector.com

ICE

INDUSTRIAL
COMMERCIAL
EQUIPMENT
MANUFACTURING LTD.

1663 Burrows Avenue
Winnipeg, MB R2X 3B5
1-888-792-0374
204-775-8252
Fax: 204-783-6794
www.frost-fighter.com